

## SuperServer E50-9AP-L



**Integrated Board**



[\(/products/motherboard/Atom/A2SAP-H.cfm\)]((/products/motherboard/Atom/A2SAP-H.cfm))

[\*\*A2SAP-H\*\*]((/products/motherboard/Atom/A2SAP-H.cfm))

**Views:** | [\*\*Angled View\*\*]((/a_images/products/views/E50-9AP-L_angle.jpg)) | [\*\*Front View\*\*]((/a_images/products/views/E50-9AP-L_front.jpg)) | [\*\*Rear View\*\*]((/a_images/products/views/E50-9AP-L_rear.jpg))

[\*\*Drivers & Utilities\*\*](#) | [\*\*BIOS\*\*](#) | [\*\*IPMI\*\*](#) | [\*\*Tested Memory\*\*](#)

[\*\*Tested M.2 List\*\*]((/en/support/resources/m2ssd?SystemID=86606&ProductName=SSE50-9AP-L))

[\*\*Manuals\*\*](#)

[\*\*OS Certification Matrix\*\*]((/support/resources/OS/OS_Certification_Intel.cfm?MProduct_Name=SYS%2DE50%2D9AP%2DL))

## Key Features

- **Cost Optimized IoT Gateway**
- **Commercial Appliance**

1. Intel® Atom® processor E3940 (9.5W, 4C)  
Single socket FCBGA 1296
2. System on Chip
3. Up to 8GB Unbuffered Non-ECC  
SO-DIMM, DDR3L-1866MHz, in 1 socket
4. 1 Half size Mini-PCIe,  
1 M.2 B-Key 2242 for SATA SSD
5. Dual LAN with Intel I210-IT
6. 2 USB 3.0, 1 HDMI
7. Fanless design
8. Lockable 12V DC 40W power adapter

Note: Image above may show a varied configuration of optional parts. Please refer to parts list for standard parts included.

## Specifications

## Product SKUs

### SYS-E50-9AP-L

SuperServer E50-9AP-L (Black)

---

## Motherboard

### Super A2SAP-H

(</products/motherboard/Atom/A2SAP-H.cfm>)

---

## Processor/Cache

### CPU

#### Intel® Atom® processor E3940

Single socket FCBGA 1296

9.5W, 4C

---

## System Memory

### Memory Capacity

Up to 8GB Unbuffered non-ECC SO-DIMM, DDR3L-1866MHz, in 1 DIMM socket

### Memory Type

DDR3L up to 1866MHz

### DIMM Sizes

8GB, 4GB

### Memory Voltage

1.35 V

---

## On-Board Devices

### Chipset

System on Chip

### Network Controllers

Dual LAN with Intel® Ethernet Controller I210-IT

### Graphics

Intel® HD Graphics

HDMI (max. resolution up to 3840 x 2160 @ 30Hz)

---

## Input / Output

### LAN

2 RJ45 Gigabit Ethernet LAN ports

### USB

2 USB 3.0 ports (rear)

### Video

1 HDMI port

---



## Chassis

### Form Factor

Proprietary

### Model

CSE-E50-L

---

## Dimensions

### Width

5.82" (148mm)

### Height

1.72" (44mm)

### Depth

4.64" (118mm)

### Package

5.5" (H) x 9.5" (W) x 8" (D)

### Weight

Gross Weight: 3.52 lbs (1.6 kg)

Net Weight: 2.2 lbs (1 kg)

### Available Colors

Black

---

## Front Panel

### Buttons

Power On/Off button

### LEDs

Power LED (Hard drive activity LED)

---

## Expansion Slots

### PCI-Express

1 Half size Mini-PCIe

### M.2

1 M.2 B-Key 2242 for storage (SATA SSD)

---

## System Cooling

### Fans

Fanless design

---

## Power Supply

40W lockable 12V DC power adapter

---

## System BIOS

### BIOS Type

AMI UEFI

---

## Management

### Software

[SuperDoctor® 5 \(/products/nfo/SMS\\_SD5.cfm\)](/products/nfo/SMS_SD5.cfm)

Watch Dog

### Power Configurations

+12V DC Power Input

ACPI Power Management

Control of power-on for recovery from AC power loss

Force Power On by Jumper

---

## Operating Environment / Compliance

### RoHS

RoHS Compliant

### Environmental Spec.

Operating Temperature:

-20°C to 50°C (-4°F to 122°F) with 0.7 m/s air flow

Non-operating Temperature:

-40°C to 70°C (-40°F to 158°F)

Operating Relative Humidity:

8% to 90% (non-condensing)

Non-operating Relative Humidity:

5% to 95% (non-condensing)

The use of industrial grade wide-temperature peripherals is

## Parts List

---

[Global SKU \(/en/products/SMC\\_global\\_skus\)](/en/products/SMC_global_skus)

---